

# STORM PRO



With a 70 pints per day capacity and a 300 CFM airflow, the Storm Pro can take care of all of your dehumidification needs, especially in restoration applications. The Pro is equipped with heavy duty wheels and a convenient handle, making it easily maneuverable in any environment. The exterior of the unit features a rugged, rotomolded exterior, plus an innovative “clam shell” cover. This unique feature makes it simple to access the internal components for maintenance and repair.



- + **INTEGRATED PUMP**
- + **EASY ACCESS TO INTERNAL COMPONENTS**
- + **MULTIPLE FILTER OPTIONS**

- + **RUGGED ROTOMOLD CONSTRUCTION**
- + **LGR TECHNOLOGY FOR ULTRA EFFICIENCY**
- + **AUTO RESTART**

Rated Condensate Capacity (80°F, 60%)	70 ppd
Rated Condensate Capacity (90°F, 90%)	149 ppd
COP	2.85L/kWh
Refrigerant	R410A
F.L.A. at Rated Conditions (80°F, 60%)	4.46A
Airflow @ 0.00" S.P.	300 CFM
Inlet Filter	MERV 8
Ducting Options	6" Outlet

Sound Level	53 dBa
Drain Tube	25'
Power Cord	20'
Operating Temperature Range	33-104°F
Operating Relative Humidity Range	21-95%
Weight	85 lbs.
Dimensions L x W x H	21.2" x 19.7" x 31
Power Supply	115V/60Hz
Warranty	1/3/5

by **ALORAIR**