

STORM ULTRA



The Storm Ultra is perfect for flood restoration and basement applications. The Ultra is powerful enough for any job with a 90 pints per day capacity, 300 CFM airflow, and an efficient 2.85 L/kWh rating. It's also equipped with multiple upgrades including a "clamshell" opening, digital display, and hot gas bypass.



- + **INTEGRATED PUMP**
- + **EASY ACCESS TO INTERNAL COMPONENTS**
- + **MULTIPLE FILTER OPTIONS**

- + **RUGGED ROTOMOLD CONSTRUCTION**
- + **LGR TECHNOLOGY FOR ULTRA EFFICIENCY**
- + **AUTO RESTART**

Rated Condensate Capacity (80°F, 60%)	90 ppd
Rated Condensate Capacity (90°F, 90%)	190 ppd
COP	2.85L/kWh
Refrigerant	R410A
F.L.A. at Rated Conditions (80°F, 60%)	5.56A
Airflow @ 0.00" S.P.	300 CFM
Inlet Filter	MERV 8
Ducting Options	6" Outlet

Sound Level	53 dBa
Drain Tube	25'
Power Cord	20'
Operating Temperature Range	33-104°F
Operating Relative Humidity Range	21-95%
Weight	93 lbs.
Dimensions L x W x H	21.2" x 19.7" x 31
Power Supply	115V/ 60Hz
Warranty	1/3/5

by **ALORAIR**